

Restructuring RELAP5-3D

2005 RELAP5 International Users Seminar

Dr. George L. Mesina & Joshua M. Hykes

September 7, 2005

Outline

- **Purpose**
- **FORTRAN 90 programming**
- **Conversion Methodology**
- **Measurements**

Purpose

- **Convert interwoven logic flow paths (spaghetti) to structured blocks of coding**
- **Improvements (according to computer industry) gained by structuring the code.**
 - **Easier to read and understand**
 - **Less time required for code development**
 - **Reduced debugging time**
 - **Reduced cost for maintenance**
- **These will lead to greater robustness**

Definition: Structured Programming

- *From General Services Administration, Federal Standard 1037C (Telecom Glossary 2000)*
- A technique for organizing and coding computer programs in which a hierarchy of modules is used, each having a single entry and a single exit point, and in which control is passed downward through the structure with no unconditional branches to higher levels of the structure.

There are three types of flow control:

- Sequential
- Test (*if* and *case*)
- Iteration (*loop*)

Definition of a “Block of Code”

- A *module* or *block of code* is a group of consecutive lines of code and/or smaller blocks that have:
 - A *single entry point* at the top
 - A *single exit point*
 - *Execution* or *control* passes downward through consecutive statements or blocks

- Examples

Structured

```
Read (IN, FMT) A
B = A/3.14159265
Write (OUT) B
```


Unstructured

```
10      Read (IN, FMT) A
        B = A/3.14159265
        Write (OUT) B
```


- The second example has more than one entry point.

Flowcharts of Structured Blocks

- **Sequential**





- **Iteration / Loop**



One entry
One exit

- **If / Case**



Structured Programming

- **Essentially, there are:**
 - **No GO TO statements (multiple entry)**
 - **No multiple returns (multiple exit)**
- **For loops, special structured GO TO statements:**
 - **EXIT** – leave loop immediately when condition occurs and resume execution with statement after end-of-loop
 - **CYCLE** – leave iteration of loop immediately and resume execution with loop's test statement

FOR_STRUCT

- **FOR_STRUCT is a commercial software package for structuring unstructured code**
 - **Applies to FORTRAN IV, FORTRAN 66, and FORTRAN 77**
 - **Does not work on FORTRAN 90 code.**
- **Reformats code it restructures, for example:**
 - **Uniform spacing conventions**
 - **Uniform indentation**
 - **Resequencing of line labels**

FOR_STRUCT Restructuring

REPLACES

if (.not. condition) go to

```
    if (.not.condition) go to 10
    Block 1
    go to 20
10 Block 2
20 continue
```

Arithmetic IF

Computed GO TO

WITH

if (condition) then

```
    if (condition) then
        Block 1
    else
        Block 2
    endif
```

IF-THEN-ELSE-ELSEIF

CASE

FOR_STRUCT Restructuring

REPLACES

- Do-loop continue statements
- Jump to end of iteration
- Jump out of loop
- Backwards go to
- Multiple returns in a subroutine

WITH

end do statement
cycle statement
exit statement
do while statement *
case statement and
a single return

* Only if it is an actual loop.

FOR_STRUCT Limitations

- Some coding is so complex that FOR_STRUCT only partially restructures it.
- FOR_STRUCT cannot process pre-compiler directives.
 - #IFDEF and #INCLUDE
- FOR_STRUCT cannot process FORTRAN 90 code.

Overcoming FOR_STRUCT limits

- **Partially restructuring**
 - Applying FOR_STRUCT to its own output further restructures complex code.
 - We used 3 iterations.
- **Pre-compiler directives**
 - After applying pre-compiler, any coding that was removed is not restructured.
 - Restructure file several times with different flags active.
 - Recombine carefully.

Methodology: Complexity Control

- **Files vary in complexity with:**
 - **Size of file**
 - **The number of different IFDEFS**
 - **The number of IFDEF branches**
 - **Nesting of IFDEFS**
- **Sorted files according number of IFDEFS and then according to size.**
 - **Process files from least complexity to greatest**
 - **Develop means to overcome each difficulty as it occurs.**

Methodology: Work in stages

- **Stage 1 – Prepare file**
 - Prepare to apply CPP and FOR_STRUCT.
- **Stage 2 – Process file**
 - Apply CPP and FOR_STRUCT
- **Stage 3 – Post-processing file**
 - Essentially, undo the preparations


Stage 1: Preparing a file

- Replace F90 derived-type variables with dummy variables.
- Associate an index number with each IFDEF.
- Make “commented copies” of IFDEFS and INCLUDES.
- Append DEFINE heading(s) to file, usually creating multiple files.
 - Combinations of DEFINES depend on:
 - Nesting
 - Mutually exclusive options

Preparing a file: Example

Original File

```
ix = vlm(mi)%vctrls
#ifdef int32
    iip = ishft(is23(ix),-30)
#endif
c Set indexes in tables
11  if (s(ix) .ge. a(iip)) go to 10
    iip = iip - 1
    go to 11
10  continue
```



Prepared File


```
ix = dummy1avctrls
Converted #ifndef 4.0.0.0 i@nt32
#ifdef int32
    iip = ishft(is23(ix),-30)
#endif
C~LIT_ON
Converted #endif 4.0.0.0
C~LIT_OFF
c Set indexes in tables
11  if (s(ix) .ge. a(iip)) go to 10
    iip = iip - 1
    go to 11
10  continue
```


Stage 2: Processing a file

- **Preprocess the file(s) with CPP**
 - **Expands INCLUDES**
 - **Eliminates some conditional code**
- **Run FOR_STRUCT iteratively on each file.**
- **Troubleshoot errors by manually changing the input or output file.**
 - **Usually involves moving an ENDIF into or out of an IFDEF block**


Processing a file: Example

After CPP




```
ix = dummy1avctrls
Converted #ifndef 4.0.0.0 i@nt32
C~LIT_ON
Converted #endif 4.0.0.0
C~LIT_OFF
c Set indexes in tables
  11  if (s(ix) .ge. a(iip)) go to 10
      iip = iip - 1
      go to 11
  10  continue
```

After FOR_STRUCT



```
ix = dummy1vctrls
Converted #ifndef 4.0.0.0 i@nt32
C~LIT_ON
Converted #endif 4.0.0.0
C~LIT_OFF
C Set indexes in tables
    do while (s(ix).lt.a(iip))
      iip = iip - 1
    end do
```




Note, the code protected with “#ifndef int32” was eliminated by CPP.

Methodology: Post Processing

- **Substitute F90 variables for dummy variables.**
- **Combine files into one complete file.**
 - **Use IFDEF indexes to match blocks of code.**
 - **Verify the number of IFDEFs did not change.**
- **Uncomment the commented copies of IFDEFS and INCLUDES.**
- **Delete the included files.**
- **Fix the undesirable formatting details that FOR_STRUCT predictably produces.**
- **Run small test set; ensure output remains same.**


Post Processing a file: Example

After FOR_STRUCT



```
ix = dummmmy1vctrls
Converted #ifndef 4.0.0.0 i@nt32
C~LIT_ON
Converted #endif 4.0.0.0
C~LIT_OFF
C Set indexes in tables
  do while (s(ix).lt.a(iip))
    iip = iip - 1
  end do
```

After Post Processing



```
ix = vlm(mi)%vctrls
#ifndef int32
  iip = ishft(is23(ix),-30)
#endif
c Set indexes tables
  do while (s(ix).lt.a(iip))
    iip = iip - 1
  end do
```

Results

- **443 files in the RELAP subdirectory restructured.**
 - **53 files need no restructuring.**
- **For the 443 restructured files:**
 - **Avg # GOTOs/subroutine**
 - **Before: 10.6, After: 5.4**
 - **Max # GOTOs in any subroutine**
 - **Before: 213, After: 146**
 - **Max # labels in any subroutine**
 - **Before: 210, After: 48**